

Legacy 105

SELECTO QC350

System Part: Legacy 105 (#QC350-3)
Replacement Part: Legacy 105-R (#QC350-2)
Rated Capacity (gallons) @ 2.2GPM Chlorine 8,000
Flow Rate: 2.2GPM Chloramine 4,000
Micron Rating: 1pm(NSF Class I)
Min./Max. Pressure: 40-125psi
Min./Max. Temp.: 40° - 100°F
Inlet/Outlet Size: 3/8" Barb Standard
Shipping Weight: 4 LBs.
Dimensions (W/D/H) 5/5/15.5"

APPLICATIONS:

UNDER SINK, RVs
WATER COOLERS

• For: Chlorine, Chloramine, Sediment,
• THMs, Organics, Tannins, Bad Tastes
AND Odor Reduction

VOLUME:
2.2GPM



FILTER BENEFITS:

Reduction of Chlorine, Chloramine, Bad Tastes and Odors, Total Organic Compounds, Tannins, and Trihalomethanes.

30 times the Chloramine reduction of a Conventional Carbon Block!

Sanitary Quick Change Cartridge Design for easy Cartridge Replacement.

DRINKING WATER CHARACTERISTICS FOR FILTER APPLICATION:

Maximum Chlorine influent: 5PPM

Maximum Chloramine influent: 2PPM

Maximum TOC influent: 3PPM

Maximum Hydrogen Sulfite: 2PPM

Maximum Iron: 3PPM

Maximum Organic Nitrogen: .5PPM

TECHNOLOGY:

Moulded High Porosity Hollow Carbon with Micro-structure & Carbon Fiber Technology with Radial Flow

DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

* Independently tested by and EPA approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class I, Chlorine, Chloramine, taste & odor.

* Field tested by Selecto for the reduction of Standard 53 Cysts, MTBE, VOCs, THMs.



Clez
Clear
water.com

selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA
800-635-4017 EXT 3 678-475-0799 EXT 3

770-532-4743

678-936-1274