

# Legacy 105

## SELECTO QC350

System Part: Legacy 105 (#QC350-3)  
Replacement Part: Legacy 105-R (#QC350-2)  
Rated Capacity (gallons) @ 2.2GPM Chlorine 8,000  
Flow Rate: 2.2GPM Chloramine 4,000  
Micron Rating: 1pm(NSF Class I)  
Min./Max. Pressure: 40-125psi  
Min./Max. Temp.: 40° - 100°F  
Inlet/Outlet Size: 3/8" Barb Standard  
Shipping Weight: 4 LBs.  
Dimensions (W/D/H) 5/5/15.5"

### APPLICATIONS:

UNDER SINK, RVs  
WATER COOLERS

• For: Chlorine, Chloramine, Sediment,  
• THMs, Organics, Tannins, Bad Tastes  
AND Odor Reduction

VOLUME:  
2.2GPM



### FILTER BENEFITS:

Reduction of Chlorine, Chloramine, Bad Tastes and Odors, Total Organic Compounds, Tannins, and Trihalomethanes.

30 times the Chloramine reduction of a Conventional Carbon Block!

Sanitary Quick Change Cartridge Design for easy Cartridge Replacement.

### DRINKING WATER CHARACTERISTICS FOR FILTER APPLICATION:

Maximum Chlorine influent: 5PPM

Maximum Chloramine influent: 2PPM

Maximum TOC influent: 3PPM

Maximum Hydrogen Sulfite: 2PPM

Maximum Iron: 3PPM

Maximum Organic Nitrogen: .5PPM

### TECHNOLOGY:

Moulded High Porosity Hollow Carbon with Micro-structure & Carbon Fiber Technology with Radial Flow

DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

\* Independently tested by and EPA approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class I, Chlorine, Chloramine, taste & odor.

\* Field tested by Selecto for the reduction of Standard 53 Cysts, MTBE, VOCs, THMs.



**Clez**  
Clear  
water.com

**selecto**

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA  
800-635-4017 EXT 3 678-475-0799 EXT 3

770-532-4743

678-936-1274