

THE CONTAMIN-EATER 710

Selecto IC600

System Part:	POE 710
Replacement Part: (CE10)	POE 710-R
Rated Capacity (gallons)	Chlorine 50,000
Flow Rate: 5GPM	Chloramine 15,000
Micron Rating:	NSF Class II
Min./Max. Pressure:	40-125psi
Min./Max. Temp.:	40°- 100°F
Inlet/Outlet Size:	3/4" Female NPT Standard
Shipping Weight:	16 Lbs.
Dimensions (W/D/H)	14/9/19"

APPLICATION:

(Point Of Entry)

WHOLE HOUSE

For: Chlorine, Chloramine, Sediment,
THMs, Organics, Tannins, Bad Tastes
AND Odor Reduction

VOLUME:

5 GPM



FILTER BENEFITS:

- Reduction of Chlorine, Chloramine, Bad Tastes and Odors, Total Organic Compounds, Tannins, and Trihalomethanes.
- 30 times the Chloramine reduction of a Conventional Carbon Block!
- Sanitary Quick Change Cartridge Design for easy Cartridge Replacement.

DRINKING WATER CHARACTERISTICS FOR FILTER APPLICATION:

Maximum Chlorine influent: 5PPM

Maximum Chloramine influent: 2PPM

Maximum TOC influent: 3PPM

Maximum Hydrogen Sulphite: 2PPM

Maximum Iron: 3PPM

Maximum Organic Nitrogen: .5PPM

TECHNOLOGY:

Moulded High Porosity Hollow Carbon with Micro-structure & Carbon Fiber Technology with Radial Flow

DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

* Independently tested by and EPA approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class II, Chlorine, Chloramine, bad tastes and odors.

* Standard 53 for the reduction of Cysts, MTBE, VOCs, THMs.



Clear
water.com

770-532-4743

678-936-1274

selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA

800-635-4017 EXT 3

678-475-0799 EXT 3