

THE CONTAMIN-EATER 714-2 with Fluoride Reduction

System Part: POE 7142+ABA
 Replacement Part: CE 7142+ABA-R
 Rated Capacity (gallons) Chlorine 140,000
 Chloramine 42,000
 Flow Rate: 10GPM
 Micron Rating:
 Min./Max. Pressure: NSF Class I
 40-125psi
 Min./Max. Temp.: 40°- 100°F
 Inlet/Outlet Size: 3/4" Female NPT Standard
 Shipping Weight: 29 LBs.
 Dimensions (W/D/H) 22/9/23"

APPLICATION:
 (Point Of Entry)
WHOLE HOUSE
 For: Chlorine, Chloramine, Sediment,
 THMs, Organics, Tannins, Bad Tastes
 AND Odor Reduction
 Reduces Fluoride
 to 1 ppm
 VOLUME:
 10 GPM

Special Order
Made only for Customers of
ezClearWater.com



FILTER BENEFITS:

- One Filter can do it all! Dirt reduction, Chemical Reduction and Chloramines reduction.
- Nylon Construction to withstand High Pressure.
- 30 times the Chloramine reduction of a Conventional Carbon Block!
- 40 times more dirt holding capacity than traditional Carbon Block Filters and other polypropylene sediment
- Sanitary Quick Change Cartridge Design for easy Cartridge Replacement.

SPECIFIED TO:

Reduce Chlorine, Chloramine, Bad Tastes and Odors
 Total Organic Compounds, Tannins, Trihalomethanes,
 Cysts, VOCs, and MTBE.

TECHNOLOGY:

Moulded High Porosity Hollow Carbon with Micro-structure & Carbon Fiber Technology with Radial Flow Patented ABA2000 Media to Reduce Fluoride.

Includes Non-Corrosive mounting bracket.

DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

* Independently tested by and EPA approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class I, Chlorine, Chloramine, bad tastes and odors.

* Standard 53 for the reduction of Cysts, MTBE, VOCs, THMs.



selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA
 800-635-4017 EXT 3 678-475-0799 EXT 3

ezClear
 water.com

770-532-4743 678-936-1274