

# THE CONTAMIN-EATER 720

System Part:	POE 720
Replacement Part:	CE 720-R
Rated Capacity (gallons)	Chlorine 100,000 Chloramine 30,000
Flow Rate: 5 GPM	
Micron Rating:	NSF Class I
Min./Max. Pressure:	40-125psi
Min./Max. Temp.:	40 - 100 F
Inlet/Outlet Size:	3/4" Female NPT Standard
Shipping Weight:	20 LBs.
Dimensions (W/D/H)	14/9/29"

## APPLICATION:

(Point Of Entry)

## WHOLE HOUSE

For: Chlorine, Chloramine, Sediment, THMs, Organics, Tannins, Bad Tastes AND Odor Reduction

## VOLUME:

5 GPM



## FILTER BENEFITS:

- One Filter can do it all! Dirt reduction, Chemical Reduction and Chloramines reduction.
- Nylon Construction to withstand High Pressure.
- 30 times the Chloramine reduction of a Conventional Carbon Block!
- 40 times more dirt holding capacity than traditional Carbon Block Filters and other polypropylene sediment
- Sanitary Quick Change Cartridge Design for easy Cartridge Replacement.

## SPECIFIED TO:

Reduce Chlorine, Chloramine, Bad Tastes and Odors Total Organic Compounds, Tannins, Trihalomethanes, Cysts, VOCs, and MTBE.

## TECHNOLOGY:

Moulded High Porosity Hollow Carbon with Micro-structure & Carbon Fiber Technology with Radial Flow

Includes Non-Corrosive mounting bracket.

DO NOT USE WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

\* Independently tested by and EPA approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class I (>.5 microns, Chlorine, Chloramine, bad tastes and odors.

\* Standard 53 for the reduction of Cysts, MTBE, VOCs, THMs.

**selecto**

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA  
800-635-4017 EXT 3



**ez**  
**Clear**  
water.com

770-532-4743

678-936-1274